


# Power Adaptors



Model Name	US315-12(US-TB3)	USE315-12(EU-TB3)	US315-12(US-Y)	USE315-12(EU-Y)
<b>Input Rating</b>				
Input Voltage	100 - 240VAC	100 - 240VAC	100 - 240VAC	100 - 240VAC
<b>Output Rating</b>				
Output Voltage	12VDC	12VDC	12VDC	12VDC
<b>Input Plug</b>				
Plug Type	US	EU	US	EU
<b>Output Plug</b>				
Connector Type	3-pin terminal Block	3-pin terminal Block	Y-Type (BT1-10V)	Y-Type (BT1-10V)
Outer Diameter	-	-	-	-
Inner Diameter	-	-	-	-
Length	-	-	-	-
<b>Physical Characteristics</b>				
Dimensions without cord (L x W x H mm)	64×50×26.5mm	64×50×26.5mm	64×50×26.5mm	64×50×26.5mm
Weight	115g	135g	110g	130g
Cord Length	1800±100mm	1800±100mm	1800±100mm	1800±100mm
<b>Environmental Limits</b>				
Operating Temperature	0 to 40°C(32 to 104 F)	0 to 40°C(32 to 104 F)	0 to 40°C(32 to 104 F)	0 to 40°C(32 to 104 F)
<b>Regulatory Approvals</b>				
Safety	UL/PSE/CE/FCC	TUV/GS/CE	UL/PSE/CE/FCC	TUV/GS/CE



Model Name	UV315-12(US-LDC)	UVE315-12(EU-LDC)	UN305-0510(US-DC)	UNE305-0510(EU-DC)
<b>Input Rating</b>				
Input Voltage	100 - 240VAC	100 - 240VAC	100 - 240VAC	100 - 240VAC
<b>Output Rating</b>				
Output Voltage	12VDC	12VDC	5VDC	5VDC
<b>Input Plug</b>				
Plug Type	US	EU	US	EU
<b>Output Plug</b>				
Connector Type	Lockable DC jack	Lockable DC jack	DC jack	DC jack
Outer Diameter	5.5	5.5	3.5	3.5
Inner Diameter	2.1	2.1	1.35	1.35
Length	9.5	9.5	7.5	7.5
<b>Physical Characteristics</b>				
Dimensions without cord (L x W x H mm)	68.1×28.1×50.8mm	68.1×28.1×50.8mm	45.5×33×23.5mm	47.8×36×27.3mm
Weight	110g	120g	70g	85g
Cord Length	1800±100mm	1800±100mm	1800±100mm	1800±100mm
<b>Environmental Limits</b>				
Operating Temperature	0 to 40°C(32 to 104 F)	0 to 40°C(32 to 104 F)	0 to 40°C(32 to 104 F)	0 to 40°C(32 to 104 F)
<b>Regulatory Approvals</b>				
Safety	UL/PSE/CE/FCC	CE	UL/PSE/BSMI/CE	CE



Atop Technologies, Inc.  
 TEL : +886-3-5508137  
 FAX : +886-3-5508131  
 sales@atop.com.tw  
 http://www.atop.com.tw

